U.S. Serial No. 10/519,437   PATENT
Reply to Notice of Non-Compliant Amendment dated June 9, 2008   Docket CU-4042

<u>**Amendments To The Claims**</u>

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

<u>**Listing of claims:**</u>

1-25. (cancelled)

26.   (**currently amended**) A semiconductor storage apparatus for realizing ~~information prompt~~ <u>information indication</u>, comprising
    a power source module providing power to the semiconductor storage apparatus **independently**;
    a controller module having a firmware for realizing the ~~information prompt~~ <u>information indication</u> and data access;
    an interface module;
    a semiconductor storage medium module having a ~~prompt information~~ <u>indication information</u> storage region for storing ~~prompt information~~ <u>indication information</u>; and
    an ~~information prompt~~ <u>information indication</u> module, wherein the controller module, the interface module, the semiconductor storage medium module, and the ~~information prompt~~ <u>information indication</u> module are electrically connected to each other.

27.   (**currently amended**) The semiconductor storage apparatus of claim 26, wherein the firmware supports [[the]] <u>a</u> password verification of the ~~prompt information~~ <u>indication information</u> storage region.

28.   (**currently amended**) The semiconductor storage apparatus of claim 26, wherein the ~~prompt information~~ <u>indication information</u> storage region is provided

Page 3 of 7

with an independent or universal encryption/decryption module, and the
encryption/decryption module encrypts the data to be stored in the ~~prompt information~~
indication information storage region, and decrypts the data read from the ~~prompt~~
~~information~~ **indication information** storage region.

29.   (original) The semiconductor storage apparatus of claim 26, wherein the
interface module is one of a USB interface, IEEE1394 interface, Bluetooth interface,
IrDA infrared interface, HomeRF interface, IEEE802.11a interface, IEEE802.11b
interface, wire wide area/local area network interface, and wireless wide area/local area
network interface.

30.   (original) The semiconductor storage apparatus of claim 26, wherein the
medium used by the semiconductor storage medium module is one of a flash memory,
DRAM, EEPROM, SRAM, FRAM, MRAM and MILLIPEDE.

31.   (**currently amended**) The semiconductor storage apparatus of claim 26,
wherein the ~~information prompt~~ **information indication** module comprises at least
one of a display component, an acoustic component and a vibration component.

32.   (original) The semiconductor storage apparatus of claim 31, wherein the display
component is one of a liquid crystal display, light-emitting diode matrix display, field
emission display and organic-electroluminescence (OEL) display; and the acoustic
generating component is one of a speaker, buzzer and crystal acoustic generator.

33.   (original) The semiconductor storage apparatus of claim 26, wherein the power
source module further comprising:
       at least one of a voltage adapter circuit; and
       a self-contained power source having a power control switch, wherein the self-
contained power source is one of a PV cell, a primary cell, and a rechargeable cell.

U.S. Serial No. 10/519,437   PATENT
Reply to Notice of Non-Compliant Amendment dated June 9, 2008   Docket CU-4042

34.   **(currently amended)** The semiconductor storage apparatus of claim 26, further comprising a manual control component for setting the ~~information prompt~~ **information indication**, wherein the manual control component is used to perform the manual control of the ~~information prompt~~ **information indication**.

35.   **(currently amended)** A method for realizing ~~information prompt~~ **information indication** in a semiconductor storage apparatus comprising a power source module providing power to the semiconductor storage apparatus; a controller module having a firmware for realizing the ~~information prompt~~ **information indication** and data access; an interface module; a semiconductor storage medium module having a ~~prompt information~~ **indication information** storage region for storing ~~prompt information~~ **indication information**; and an ~~information prompt~~ **information indication** module, wherein the control module, the interface module, the semiconductor storage medium module, and the ~~information prompt~~ **information indication** module are electrically connected to each other, the method comprising:
          performing data access operation of the ~~prompt information~~ **indication information** storage region and the ~~information prompt~~ **information indication**;
          verifying [[the]] --a-- password of the ~~prompt information~~ **indication information** storage region according to [[the]] --a-- predetermined setting, and
          after the step of verifying the password, obtaining [[the]] --a-- necessary ~~prompt information~~ **indication information** from the ~~prompt information~~ **indication information** storage region; and
          controlling the ~~information prompt~~ **information indication** module to ~~perform the information prompt~~ **indicating the information** based on the content of the obtained ~~prompt information~~ **indication information**.

36.   **(currently amended)** A method for realizing ~~information prompt~~ **information indication** of claim 35, further comprising the step of writing the necessary ~~prompt information~~ **indication information** into the ~~prompt information~~ **indication information** storage region after verifying the password.

U.S. Serial No. 10/519,437   **PATENT**
Reply to Notice of Non-Compliant Amendment dated June 9, 2008   Docket CU-4042

37.   **(currently amended)** A method for realizing ~~information-prompt~~ **information indication** of claim 35 wherein [[the]] --an-- operational mode of the ~~information-prompt~~-**information indication** module and the ~~prompt-information~~ **indication information** stored in the ~~prompt-information~~-**indication information** storage region is defined and modified by ~~the information-prompt~~ **an information indication** storage region setting software running in the data processing system.

38.   **(currently amended)** A method for realizing ~~information-prompt~~ **information indication** of claim 35, wherein the ~~prompt-information~~-**indication information** comprises static information and dynamic information, wherein the static information comprises the user's information, device information and storage information.

39.   **(currently amended)** A method for realizing ~~information-prompt~~ **information indication** of claim 36, wherein the ~~prompt-information~~-**indication information** comprises static information and dynamic information, wherein the static information comprises the user's information, device information and storage information.

40.   **(currently amended)** A method for realizing ~~information-prompt~~ **information indication** of claim 37, wherein the ~~prompt-information~~-**indication information** comprises static information and dynamic information, wherein the static information comprises the user's information, device information and storage information.

41.   **(currently amended)** A method for realizing ~~information-prompt~~ **information indication** claim 35, ~~wherein~~ **further comprising the steps of encrypting the data to be stored in the indication information storage region, and decrypting the data read from the indication information storage region by an**

independent or universal encryption/decryption module provided in ~~the prompt~~
~~Information~~ the indication information storage region ~~is provided with a~~
~~Independent or universal encryption/decryption module, the~~
~~encryption/decryption module encrypts the data to be stored in the prompt~~
~~information storage region, and decrypts the data read from the prompt~~
~~information storage region~~.